



Neptune LED Street Light



Heavy extruded aluminum alloy housing

Features:

- Professionally designed optical lens with beam angle 80×155°
- Bat wing light distribution curve, light more widely transmitted
- The bracket is adjustable 90-180 degree
- · Heavy extruded aluminum alloy housing
- Multi ribs design for more efficient heat dissipation
- Apply for unique surface treatment technology, well-decorated
- Easy to install, lower maintenance cost and wide in application.
- Waterproof IP65

Materials:

- · Body: Aluminum
- Cover: PC

Options:

- 1-10V
- DALI

Colors:

Sliver

Accessory:



Bracket








Item Code				Description				
	Power w	Voltage vac	Frequency hz	Lumen Flux Im	Color Temp k	CRI ra	Operating c°	Warranty yrs
SL-A50W	50	85-265	50/60	6000±5%	ww nw cw	80	-40 ~ +50	5
SL-A100W	100	85-265	50/60	12000±5%	ww nw cw	80	-40 ~ +50	5
SL-A150W	150	85-265	50/60	18000±5%	ww nw cw	80	-40 ~ +50	5
SL-A200W	200	85-265	50/60	24000±5%	ww nw cw	80	-40 ~ +50	5
SL-A250W	250	85-265	50/60	30000±5%	ww nw cw	80	-40 ~ +50	5
SL-A300W	300	85-265	50/60	36000±5%	ww nw cw	80	-40 ~ +50	5

Neptune LED Street Light

Light distributions:

Light distribution curve



Dimensions (unit mm)

